



## 2004 E-Z-GO Shuttle 2 + 2 TXT Electric

---

### STANDARD EQUIPMENT:

**Motor:** 36 volt DC high efficiency series wound, brazed armature, solid copper windings.  
**Drive Train:** Direct motor shaft connected to transaxle pinion shaft.  
**Electrical System:** 36 volt DC, six, 6 volt deep cycle storage batteries (107 minute, 220 amp-hour @ 20 Hr. discharge rate). Dash mounted electronic "state of charge" meter.  
**Speed Control:** Solid state continuously variable speed controller. 300 Amp capacity. Non-contact inductive throttle sensor.  
**Charger:** Powerwise™ portable fully automatic line compensating, 21 amp DC output at 36 volts; input 120 volts, 9.5 amps, 60 cycle AC, Underwriters Laboratories (U.L.) Listed, C.S.A. Certified, anti drive away charger/vehicle interlock.  
**Transaxle:** High efficiency helical gears, 12.44:1 ratio.  
**Brakes:** Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings. Automatic park brake release with self-compensating system.  
**Front Suspension:** Leaf springs with hydraulic shock absorbers.  
**Rear Suspension:** Heavy duty leaf springs with hydraulic shock absorbers.  
**Steering:** Self-compensating single reduction rack and pinion.  
**Speed:** 12 - 14 MPH (19 - 23 KPH)  
**Lighting:** Headlights, taillights, brake lights and horn.

---

### DIMENSIONAL SPECIFICATIONS:

**Weight:** 646 lbs. (293 KG), without batteries  
**Length:** 105.0 inches (2.67m) (including foot rest)  
**Width:** 46.5 inches (1.18m)  
**Height:** 48.6 inches (1.23m) at steering wheel  
**Wheel Base:** 65.5 inches (1.66m)  
**Front Wheel Tread:** 33.5 inches (0.85m)  
**Rear Wheel Tread:** 38.0 inches (0.97m)  
**Clearance Circle:** 18.9 feet (5.72m)  
**Tires:** 18 x 8.50 x 8 (4 ply rated)  
**Load Capacity:** 800 lbs. (362 KG) including operator, passengers, accessories and cargo.  
**Seating:** Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and three passengers.

---

### FEATURES:

- 1. Body & Finish:** Durashield™ body of automotive quality injection molded TPE (thermoplastic elastomer). Molded-in color with automotive color coat/clear coat finish.
- 2. Chassis:** Welded high yield strength tubular steel with Durashield™ powder coat paint.
- 3. Safety:** Dash mounted key switch, reverse warning indicator, "deadman" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector with "neutral".
- 4. Dash Panel:** Tee, ball, and 4 position drink holders of scuff resistant glass fiber reinforced thermoplastic olefin.
- 5. Steering Wheel:** Hi-tech design with dual handgrips, pencil holder, integral scorecard holder.
- 6. Flip-up Rear Seat:** For storage access.

---

### ACCESSORIES:

Sun Canopy With Handles

Wheel Covers:

Chrome Hub Cap 6", 8"

Gold Spoke

Silver Spoke

Front Windshield, Tinted

Front Windshield, Clear

Turn Signal Kit

---

### OPTIONS:

See your local distributor.