



A Textron Company

2004 E-Z-GO Shuttle 4 TXT Electric

STANDARD EQUIPMENT:

Motor: 48 volt DC high efficiency series wound, brazed armature, solid copper windings.

Drive Train: Direct motor shaft connected to transaxle pinion shaft.

Electrical System: 48 volt DC, eight, 6 volt deep cycle storage batteries (107 minute, 220 amp-hour @ 20 Hr. discharge rate). Dash mounted electronic "state of charge" meter.

Speed Control: Solid state continuously variable speed controller. 350 Amp capacity. Non-contact inductive throttle sensor.

Charger: Fully automatic line compensating, 21 amp DC output at 48 volts; input 110-120 volts, 60 cycle AC

Transaxle: High efficiency helical gears, 14.7:1 ratio.

Brakes: Hydraulic drum type rear wheel brakes. Foot operated parking brake. Non asbestos lining.

Front Suspension: Heavy duty leaf springs with hydraulic shock absorbers.

Rear Suspension: Heavy duty leaf springs with hydraulic shock absorbers.

Steering: Self-compensating single reduction rack and pinion.

Speed: 12 MPH (19 KPH)

DIMENSIONAL SPECIFICATIONS:

Weight: 710 lbs. (322 KG), without batteries

Length: 133 inches (3.38m)

Width: 46.5 inches (1.18m)

Height: 48.6 inches (1.23m) at steering wheel

Top Height: 73.0" (1.85m)

Wheel Base: 93.5 inches (2.37m)

Front Wheel Tread: 33.5 inches (0.85m)

Rear Wheel Tread: 38.0 inches (0.97m)

Outside Clearance Circle: 29 feet (8.8m)

Tires: 18 x 8.50 x 8 (4 ply rated)

Load Capacity: 1,200 lbs. (544 KG) including operator, passengers, accessories and cargo.

Seating: Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and three passengers.

Bed Size: 42.5 inches wide x 32 inches long (1.08m x .8m)

FEATURES:

- 1. Body & Finish:** Durashield™ body of automotive quality injection molded TPE (thermoplastic elastomer). Molded-in color with automotive color coat/clear coat finish.
- 2. Chassis:** Welded high yield strength tubular steel with Durashield™ powder coat paint.
- 3. Safety:** Dash mounted key switch, reverse warning indicator, "deadman" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector, horn.
- 4. Dash Panel:** 4 position drink holders of scuff resistant glass fiber reinforced thermoplastic olefin.
- 5. Steering Wheel:** Hi-tech design with dual handgrips, pencil holder, and clip/holder.
- 6. Convenience Items:** Center position grab handle for rear seat passengers, cargo bed with wood stake side kit.

ACCESSORIES:

Sun Canopy With Handles

Wheel Covers:

Chrome Hub Cap 6", 8"

Gold Spoke

Silver Spoke

Front Windshield, Tinted

Front Windshield, Clear

Light Package - Headlights, Taillights, Brake lights

Turn Signal Kit (front & rear)

OPTIONS:

See your local distributor.

Revised 10/17/03

2004_shuttle_4_txt_electric.doc

Specifications subject to change without notice.